# A2 System by Blue Acoustic®



The A10 is a superbly compact powered loudspeaker operating in bi-amplified mode and is the top box in our Blue Acoustic A2 System.

It's partnered with the M2B single 15" powered bass unit also used as the bass unit in our M2 System.

A10 has the power and ability to be thoroughly effective yet neatly unobtrusive in a vast variety of premium events however, it's also an alternative for customers who prefer a more conventional cabinet in their rig.

**Blue Acoustic** loudspeakers incorporate not only some of the finest components currently available but those that are fully proven within the professional environment.

#### 294 A10 component specifications. k 270mm (10") bass unit bass unit aes power 400 watts bass unit voice coil 63mm (2.5") (4Ω) bass unit magnet neodymium hf unit exit 25·4mm (1") hf unit aes power 60 watts hf unit voice coil **44mm** (8Ω) hf unit magnet neodymium 80° x 60° (aluminium) horn unit 526 module power (bass/mid) **390 watts aes** $(@4\Omega)$ module power (hf) **60 watts aes** (@ 16Ω) module control factory configured dsp module presets 4 in total THD+N <0.01% 0.1w to full power > 1,000 @ 100Hz damping factor 1.6KHz (L/R @ -6dB points) crossover centre frequency A10 cabinet specifications. handle top mounted dual lift pole mount 35mm vertical and 5° tilt forward 12mm, 18mm and 24mm birch ply build material 不 bass/mid efficiency 1w/1m 98dB 108dB hf efficiency on horn used 1w/1m spl at rated power 124dB tml (theoretical max level) \* 130dB frequency response (preset 1) 59Hz - 18.4Khz (± 3dB) high pass filter (full range) 50Hz (8th order) 294 high pass filter (with bass cabs) 115Hz (4th order) mains input voltage 110-240v Neutrik Powercon A mains connection mains onward link Neutrik Powercon B signal input connector XLR 3 (cable male to female socket) signal link connector XLR 3 (cable female from male socket) dimensions 526 h x 294 w x 294 d 13-9 Kgs (30.6 lbs) weight slip over padded versions covers

\* tml is published for comparative purposes only

Blue Acoustic is a Trade Mark registered in the United Kingdom - number UK02517676 Trade Mark used with the permission of the owners purely upon Blue Acoustic products. All designs and settings copyright Ken Hughes - 2015.

### Blue Acoustic<sup>®</sup>; where less is more

## A2 System by Blue Acoustic®

383mm (15")

**102mm**(4") (8Ω)

>1,000@100Hz

700 watts aes (@ 8Ω)

factory configured dsp

<0.01% 0.1w to full power

115Hz (L/R @ -6dB points)

700 watts

ferrite

4 in total



The M2B is again used in another compact Blue Acoustic system.

This time it's operating within the same single channel module as the bass box in the **Blue Acoustic A2 System** and partnered with the **A10** single 10"/1" powered top unit detailed overleaf.

Using it's superb single channel Powersoft module the M2B has the power and ability to be thoroughly effective yet neatly unobtrusive in a vast variety of premium events.

**Blue Acoustic** loudspeakers incorporate some of the finest premium quality drive units and amplifier modules.

### M2B component specifications.

bass unit bass unit aes power bass unit voice coil bass unit magnet module power (bass) module control module presets THD+N damping factor crossover centre frequency

### M2B cabinet specifications.

handles dual lift on sides, top and bottom 20mm screw thread pole mount castors 100mm swivel type build material 18mm and 24mm birch ply bass driver efficiency 1w/1m 97dB spl at rated power 125dB tml (theoretical max level) \* 131 dB frequency response (preset 1) 44 - 135hz (± 3dB) 40Hz (8th order) high pass filter 110-240v mains input voltage mains connection **Neutrik Powercon A** mains onward link **Neutrik Powercon B** signal input connector XLR 3 (cable male to female socket) signal link connector XLR 3 (cable female from male socket) dimensions  $582 h \times 442 w \times 500 d$ weight 28-2 Kgs (62 lbs) cover slip over padded versions accessories SubSafe<sup>®</sup> bass covers available

442

K

\* tml is published for comparative purposes only

#### **Blue Acoustic Sales - Europe**

Units 3 & 6, Grooms Building, Pool Road, Newtown, Powys SY16 1DL Tel: +44 (0) 1686 622368 Mob: 07971 882663 Email: <u>ken@blue-acoustic.com</u>

**Blue Acoustic Sales - USA** 

Tulsa, OK, 74146 Tel: **(918) 732 9343** Email: info@blueacousticusa.com

Blue Acoustic is a Trade Mark registered in the United Kingdom - number UK 02517676 Trade Mark used with the permission of the owners purely upon Blue Acoustic products. All designs and settings copyright Ken Hughes - 2016.

Blue Acoustic<sup>®</sup>; where less is more